



## THREE PROCESSES, ONE POWER SOURCE

/ MIG, TIG and Stick

/ Over 60 pre-programmed waveforms available for GMAW

/ TIG Pulsing Capabilities with amperage adjustment on the torch

/ The MIG Spot/Stitch mode provides easy use for out of position welding and thin sheet metal



### STATIONARY AND PORTABLE

/ Suitable for fabrication shops, construction sites and assembly work

/ Easy to move – 33.5 lbs

/ Optional carrying strap

/ Skid runners on the side panels for durability in the field

/ Extension cords of up to 300 +ft without tripping breakers



### SIMPLE TO OPERATE

/ Synergic Based Welding - Set material thickness and machine is ready to weld

/ Adaptive arc will compensate for stick-out change automatically

/ 2 program slots for your favorite weld settings

/ Parameters can be changed through turn/press function



#### THE MOST COMPACT TRANSSTEEL

/ Internal wire feeder accommodates 10 lb and 2 lb wire spools

/ Newly developed two-roller motor plate for stable wirefeed

/ Wearing parts box inside the power source

# 24 DIFFERENT WELDING TASKS A DAY, ONE POWER SOURCE FOR THEM ALL.

For the TransSteel 2200, it's all the same. Construction site or fabrication shop. Machine and steel construction or pipeline and crane construction. Rolling stock or containers. The TransSteel 2200 easily masters MIG, TIG and Stick welding to the same high level.

So what's your welding challenge?

Let's get connected.







# **PROPERTIES**

MIG	TIG	STICK
Up to 220 A	Up to 230 A	Up to 180 A
Ø 0.30" – 0.045"	LiftArc ignition	Ø 1/16" – 5/32"
Steel, Aluminum, Stainless Steel characteristics	Pulse welding	Perfect ignition properties without sticking
Spot and interval welding	TAC function	-Not for 6010 rods

/ 33.5 lbs
/ Multivoltage 120 – 230 V
/ Duty cycle 30% (220 A)
/ Steel, Stainless Steel, Silicon Bronze, Flux Cored,
Metal-Cored, Self-Shielded, Aluminum
/ Up to 0.045" wire diameter

Mains Voltage	1x120Vac	1 x 120Vac	1x240Vac
	(-20% / +15%)	(-20% / +15%)	(-20% / +15%)
Fuse protection	15A (slow blow)	20A (slow-blow)	15A (slow-blow)
Generator power	3.2 kW	4.7kW	8.4 kW
Power cable	AWG 14 (included)	AWG 14 (included)	AWG 14 (included)
MIG Voltage	14.5 - 24.5 Vdc	14.5 - 24.5 Vdc	14.5 - 24.5 Vdc
Current	10 - 105A	10 - 135A	10 - 210A
Stick Voltage	20.4 - 27.2 Vdc	20.4 - 27.2 Vdc	20.4 - 27.2 Vdc
Current	10 - 90A	10 - 110A	10 - 180A
TIG Voltage	10.4 - 19.2 Vdc	10.4 - 19.2 Vdc	10.4 - 19.2 Vdc
Current	10 - 135A	10 - 160A	10 - 230A
Duty Cycle	30% / 60% / 100%	30% / 60% / 100%	30% / 60% / 100%
MIG (104°) (77°)	105A / 95A / 80A	135A / 120A / 105A	210A / 170A / 150A
	105A / 105A / 105A	135A / 120A / 105A	210A / 170A / 150A

Order with package number at your preferred Fronius Distributor	Package number
TST2200 MV Gas-cooled MIG/TIG/ Stick standard package, includes: TIG & MIG Torches, stinger, ground cable, clamp, gas regulator, consumable setup .030 and .035 Pre-assembled and tested	49,0400,0034
TST2200 MV Gas-cooled MIG /Stick standard package, includes: MIG Torch, stinger, ground cable, clamp, gas regulator, consumable setup .030 and .035 Pre-assembled and tested	49,0400,0033

Fronius USA LLC Headquarters 6797 Fronius Drive Portage, IN 46368 United States (877) Fronius (376-6487) sales.usa@fronius.com www.fronius.us

North East 10421 Citation Drive Brighton, MI 48116 United States (810) 844-2800 sales.northeast@fronius.com www.fronius.us South East 1271 N Holtzclaw Ave Chattanooga, TN 37406 United States (423) 697-1777 sales.southeast@fronius.com www.fronius.us South Central 8715 Fallbrook Houston, Texas 77064 United States (219) 734-5500 sales.southcentral@fronius.com www.fronius.us California 2900 Adams A-30 Riverside, CA 92504 United States (219) 734-5500 sales.california@fronius.com www.fronius.us